



Automatic Monitor Nozzle 300-1000 GPM

Features

- Manufactured in Light Weight Aluminum
- Standard optimum operating pressure 100 psi (7 Bar)
- Supplied w/2-1/2" swivel FNST inlet
- Reacts automatically to change in flow
- Fixed turbine teeth
- Large rubber bumper
- Pattern easily changed with large control handles
- Maintains a consistent operating pressure over a wide flow range



Suitable

- Suitable for use with water, AFFF, or AR-AFFF foam solutions
- Ideal for use on Portable and Fixed Monitors

Part No:	PSI	Inlet	GPM(lpm)	Material	Length(cm)	Weight(kg)
CN-A1000	100 PSI (7 Bar)	2.5" FNST	300-1000 (1140-3800)	Chemlite	8" (20)	12 lbs. (5.4)

Flow Chart

Nozzle Pressure	Range	Flow Rate
100 psi (7.0 bar)	180 ft (55 m)	300 gpm (1140 lpm)
100 psi (7.0 bar)	210 ft. (64 m)	500 gpm (1900 lpm)
100 psi (7.0 bar)	240 ft. (73 m)	1000 gpm (3800 lpm)

CHEMGUARD
 204 S. 6th Ave • Mansfield, Tx 76063 • (817) 473-9964 • FAX (817) 473-0606
www.chemguard.com