

WHEELED FIRE EXTINGUISHERS

Series 4500

DRY CHEMICAL:

Carts and framing components are made of rugged steel. All brass cylinder valve and hose valve assemblies are chrome plated. Hoses are quick release and non-kinking.

CARBON DIOXIDE:

Spun steel cylinder-brass chrome plated valves. Designed for one person operation. Reinforced wire braided hose. Pneumatic tires 16" X 4".

REGULAR DRY CHEMICAL:

Carts and framing components are made of rugged steel. All brass cylinder valve and hose valve are chrome plated. Quick release non-kinking hoses.

HALOTRON:

Cylinders with chrome plated brass valve. Equipped with all weather semi-pneumatic 16" diameter 4" wide tires for easy moveability.



Figure No. 4510



Figure No. 4580



Figure No. 4530

All Types and Sizes of Wheeled extinguishers are available upon request.

| Figure No. | Type | Use | U/L Rating | Capacity | Discharge time (sec) | Discharge Range | Hose Length | Height | Dimensions Width | Depth | Shipping Weight |
|------------|----------------------|-----|------------|----------|----------------------|-----------------|-------------|--------|------------------|-------|-----------------|
| 4510 | Dry Chemical ABC | | 20A-160B:C | 50 | 35 | 25-35 | 25' | 47 | 21.5 | 24.6 | 174 Lbs. |
| 4520 | Dry Chemical ABC | | 30A-240B:C | 125 | 48 | 30-40 | 50' | 50 1/2 | 28.7 | 40.1 | 344 Lbs. |
| 4530 | CO2 | | 20 B:C | 50 | 44 | 15 | 15' | 60 | 48 | 23.5 | 257lbs. |
| 4535 | CO2 | | 20 B:C | 100 | 74 | 15 | 40' | 65 | 30 | 21 | 461 Lbs. |
| 4570 | Regular Dry Chemical | | 240BC | 150 | 48 | 30-40 | 50' | 50 | 28.7 | 40.1 | 369 Lbs. |
| 4580 | Halotron | | 4A-40BC | 65 | 22 | 30-45 | 50' | 58 | 28.7 | 41.5 | 300 Lbs. |
| 4590 | Halotron | | 10A-80BC | 150 | 38 | 30-45 | 50' | 64 | 30.7 | 41.5 | 480 Lbs. |