



Figure No. 4830

CLASS D DRY POWDER

SERIES 4800

**U/L LISTED DFM APPROVED
STANDARD EQUIPMENT:**

Corrosion resistant yellow (Class D) Color Coded. Painted Finish. Unique soft flow extension applicator and built in long range nozzle.

IDEAL USES:

Metal fires containing magnesium, sodium, uranium and aluminum.

- 4830 Class D Sodium Chloride Powder
- 4832 Class D Copper Powder



WET CHEMICAL

SERIES 4800

**U/L LISTED
STANDARD EQUIPMENT:**

Contain a blend of Potassium Acetate and Citrate.

IDEAL USES:

Kitchen cooking oil fires. Great in fighting and cooling very hot and difficult fires.



Figure No. 4834

Figure No.	U/L Rating	Capacity (lbs.)	Height	Width	Depth (dia.)	Valve Material	Cylinder Material	Coast Guard Approved	Bracket	Shipping Weight (lbs.)
4830	D	30 Lbs.	32"	13"	8"	Brass	Steel	No	Wall	53 Lbs.
4832	D	30 Lbs.	32"	13"	8"	Brass	Steel	No	Wall	53 Lbs.
4834	K	6 Ltrs..	19"	9"	7"	Chr. Pl. Brass	Stainless Steel	No	Wall	22 1/2Lbs.

VEHICLE BRACKETS

STANDARD EQUIPMENT:

Brackets are steel with a primed polyester powder paint finish.



Figure No. 4835



Figure No. 4836

Figure No.	For Use with the following Extinguishers	Color
4835	4005	Red
4836	4010	Red
4837	Advise Size of Extinguisher	Red



Figure No. 4837



OTHER BRACKETS AVAILABLE UPON REQUEST